

# Element He27X

## 2-in-1 Hybrid POS



The Element He27X Series provides, a 2-in-1 Hybrid POS offering a single device to provide you a fixed or a mobile point-of-service solution to meet your customer and business needs.

The Element He27X has an aesthetic metallic design that is highly functional, ultra-slim and ergonomic. With an 11.6" FHD screen and optional in-built 2D barcode scanner and optional side attachment peripherals including: MSR, iButton, Fingerprint Reader, RFID and Rear 5MP Camera, the He27X is an impressive multifunction solution to suit a variety of business applications.

The Element HE276 is the next evolution of retail and hospitality technology. Take the point of service to your customer, consolidate multiple business functions into a single device, and reduce hardware overhead. A true 2-in-1 hybrid POS built for the way modern hospitality operates.



### Key Features

- ✓ 2-in-1 multifunctional POS
- ✓ Ultra-slim & ergonomic design
- ✓ Aesthetic metallic design
- ✓ 11.6" Touch Screen
- ✓ Windows 11 IOT, Intel® Elkhart Lake Celeron J6412
- ✓ Standard features of WiFi, Bluetooth with slim, ergonomic retail docking station providing additional USB ports, Comm ports, LAN, and Cash Drawer ports
- ✓ Magnetic lock design
- ✓ Rotatable screen for multiple angles

# Element He27X

## SPECIFICATIONS

<b>MODEL</b>	Element He27X
Processor	Intel® Elkhart Lake Celeron J6412
RAM Memory	8GB DDR4
HDD & SSD	128GB eMMC
Touchscreen	11.6" 1920 × 1080 FHD, PCAP multi-touch, 300 nits
Compatible OS	Windows 11 IoT Enterprise LTSC
Speaker	1 × 1W Internal Speaker
Battery	3.85V / 7000mAh
Colour	Black (metallic chassis)
Communication	Wi-Fi 802.11 a/b/g/n/ac, Bluetooth 4.0 + LE
EMC & Safety	FCC Class B, CE Mark Class B, LVD, RF
Dimensions	He276: 276 × 179 × 15.4 mm (10.9" x 7" x 0.6")

<b>I/O PORTS</b>	<b>Basic Stand</b>	<b>Premium Stand</b>
USB	3x USB2.0 Type A 1x USB2.0 Type C	1x USB3.0 Type C 2x USB3.0 1x USB2.0
Powered USB	1× 12V 1× 24V	1× 12V 1× 24V
Serial Port	2x DB9 (default 0V, 5V;12V)	2x DB9 (COM1: 0V*/5V/12V, COM2: 0V*/5V/12V)
LAN	1x RJ45 (10/100 Mbps)	1x RJ45 (1 Giga LAN)
Cash Drawer	1 x RJ11	
DC Jack	1× 4PIN	
Power Adapter	120W / 19V	

## ENVIRONMENT

Operating Temp	0°C ~ 35°C (32°F ~ 95°F)
Storage Temp	-20°C ~ 60°C (-4°F ~ 140°F)
Humidity	20% ~ 80% RH non-condensing

✉ [sales@triniteq.com](mailto:sales@triniteq.com)

🌐 [www.triniteq.com](http://www.triniteq.com)

☎ 1300 784 666

